

(19) World Intellectual Property  
Organization  
International Bureau



543011

(43) International Publication Date  
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number  
**WO 2004/070357 A1**

(51) International Patent Classification<sup>7</sup>: **G01N 1/38**

(74) Agent: **OUTOKUMPU OYJ**; Intellectual Property Management, P.O. Box 27, FIN-02201 Espoo (FI).

(21) International Application Number:  
PCT/FI2004/000055

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 4 February 2004 (04.02.2004)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:  
20030173 5 February 2003 (05.02.2003) FI

(71) Applicant (*for all designated States except US*): **OUTOKUMPU OYJ** [FI/FI]; Riihitontuntie 7, FIN-02200 Espoo (FI).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **VON ALFTHAN, Christian** [FI/FI]; Turuntie 167 C, FIN-02710 Espoo (FI).

[Continued on next page]

(54) Title: **DEVICE FOR A CONTINUOUSLY OPERATED DILUTING OF A SLURRY SAMPLE**



(57) Abstract: This invention relates to a device for a continuously operated dilution of a slurry sample, through which device the slurry sample is fed directly into a continuously operated optical analyzer, such as a grain size analyzer. The device comprises elements for feeding the slurry sample, elements for feeding diluting liquid and elements for removing solids contained in the slurry, as well as elements for discharging both the liquid contained in the slurry and the liquid used for dilution. The device of the invention comprises at least one downwardly narrowing chamber (2,31) that is connected to the analyzer measurement cell (3, 34) so that two opposite walls (10, 32) of the chamber (2, 31) are essentially parallel both with respect to each other and with respect to the respective walls (21, 35) of the measurement cell (3, 34).

WO 2004/070357 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD,

SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

- *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## DEVICE FOR A CONTINUOUSLY OPERATED DILUTING OF A SLURRY SAMPLE

The present invention relates to a device for a continuously operated diluting of  
5 a slurry sample, through which device the slurry sample is fed directly to a  
continuously operated optical analyzer, such as a grain size analyzer.

In the analysis of slurry samples, certain measurements, such as optical grain  
size measurements, require that the solids contained in the slurry samples is  
10 diluted down to a tenth or even to a hundredth part of the original content. From  
the US patent 6,286,376, there is known a particle size analyzer where a slurry  
sample is conducted onto an inclined surface, from which water fed in as a  
continuous flow washes the sample away, simultaneously diluting it. The initially  
diluted sample is diluted further with water continuously supplied in a funnel,  
15 from which the diluted sample is conducted, by making use of gravity, along a  
conduit to a particle size analyzer. Said conduit may include a mixing chamber,  
to which water is likewise continuously supplied in order to further dilute the  
sample. The diluting steps of said US patent 6,286,376 are carried out in  
separate dilution units that are interconnected by intermediation of conduits.

20

The object of the present invention is to eliminate some of the drawbacks of the  
prior art and to achieve an improved device that is more secure in operation for  
diluting a slurry sample in continuous operation, through which device the slurry  
sample can be directly fed into a continuously operated analyzer, such as an  
25 optical grain size analyzer. The essential novel features of the invention are  
enlisted in the appended claims.

According to the invention, from the slurry flow to be analyzed, there is  
extracted a sample by a sampling device, and said sample is diluted in the  
30 device according to the invention prior to conducting it into analysis,  
advantageously for instance in an optically operated grain size analyzer. From  
the slurry flow to be analyzed, there is extracted a solids-containing sample

preferably by a sample cutter in an essentially continuous operation. The obtained slurry sample flow is conducted into a diluting device, compiled of one or several, advantageously two, downwardly narrowing and mechanically interconnected chambers that are in liquid contact and at least partly filled with liquid such as water. In an embodiment with two chambers, the solids-containing slurry sample to be analyzed is fed into the first chamber, the supply chamber, and the solids to be analyzed are removed from the diluting device according to the invention through the second chamber, the discharge chamber. When using one chamber in the diluting chamber according to the invention, the chamber serves both as a supply chamber and a discharge chamber.

In the diluting device according to the invention, the sample slurry flow is conducted from the sample cutter serving as the sampler to an inclined surface arranged in the open top part of the diluting device. The inclined surface is advantageously aligned so that the inclined surface is positioned, throughout the operation of the diluting device, above the surface of the liquid contained in the diluting device. However, the inclined surface may also be at least partly covered by the liquid fed in the chamber. At the bottom part, the diluting device is attached to a measurement cell, made of a transparent material, of the continuously operated analyzer, such as an optical grain size analyzer, so that the cross-sectional area of the discharge aperture placed in the bottom part of the diluting device essentially corresponds to the cross-sectional area of the measurement cell having the shape of a rectangular prism. In addition, two opposite walls of the diluting device walls connected to the discharge aperture of the diluting device are installed in parallel with respect to each other, advantageously in the vertical direction, and so that said opposite walls are further parallel and essentially equal in width also with the corresponding walls of the measurement cell. In order to connect the diluting device to the measurement cell, there can also be used a separate adjusting piece or adjusting pieces, so that possible flow defects between the diluting device and the measurement cell can be avoided.

In the diluting device according to the invention, there is installed at least one liquid conduit in order to feed the diluting liquid, so that the liquid conduit is installed essentially symmetrically with respect to the walls of the chamber  
5 constituting the diluting device. The liquid conduit is provided with at least one nozzle element, through which the diluting liquid is fed into the liquid contained in the diluting device, so that agitation is created in the liquid in order to efficiently process the solids fed in along with the sample slurry flow before the solids flow into the measurement cell of the analyzer.

10

When using two chambers in the diluting device, the first chamber of the diluting device is also the upper chamber thereof, and the slurry flow is conducted to the top part of said upper chamber from the sample cutter serving as the sampler. The second chamber of the diluting device, which at the same  
15 time is the lower chamber of the diluting device, is mechanically connected to the measurement cell installed underneath the chamber and made of a transparent material. With respect to each other, the first and second chambers of the diluting device are advantageously arranged so that the bottom part of the first chamber is connected to the top part of the second chamber. Two  
20 chambers can advantageously be utilized for instance in cases where a remarkable degree of diluting is required. In that case, owing to the larger volume of the two chambers, the diluting is essentially easier.

In shape, the first chamber of the device according to the invention is  
25 downwardly narrowing, so that the shape advantageously corresponds to a truncated pyramid or cone, for example, the bottom of said pyramid or cone being the top part of the chamber, and the truncated spot being the bottom part of the chamber. The slurry sample containing the solid material is fed into the first chamber through the top part of the chamber, advantageously onto an  
30 inclined surface arranged inside the chamber. The inclined surface is arranged so that it is located above the liquid surface essentially throughout the operation of the device. However, the inclined surface may also be at least partly covered

by the liquid fed in the chamber. Through the essentially open top part of the first chamber, in the chamber there is installed at least one liquid conduit for feeding the diluting liquid, so that said liquid conduit extends, through the gap between the first and second chambers, to the second chamber. The liquid  
5 conduit is arranged in the middle of the first and second chambers, so that the liquid conduit is in an essentially symmetrical position with respect to the chamber walls. In case for instance two liquid conduits are used, the first liquid conduit can extend only to the first chamber and the second liquid conduit only to the second chamber through the first chamber.

10

In shape, also the second chamber of the device according to the invention is downwardly narrowing. Advantageously the top part of the second chamber is rectangular, but in area larger than the bottom part of the first chamber. The difference in the areas is advantageously achieved by means of the design of a  
15 flange connected to the top part of the second chamber, or, when necessary, by means of a separate adjusting piece.

The downwardly narrowing shape of the second chamber is achieved so that when the top part of the channel is rectangular, two opposite walls are arranged  
20 to approach each other towards the solids discharge aperture. On the other hand, the other two opposite walls of the chamber are arranged in an essentially parallel direction with respect to each other. In the bottom part of the chamber, the walls of the second chamber form an aperture that is essentially equal in size as the aperture provided in the top part of the analyzer  
25 measurement cell. In addition, the two essentially parallel walls of the second chamber are parallel with the corresponding walls of the analyzer measurement cell. Now the chamber and the measurement cell can be mechanically and directly interconnected, and the solids to be analyzed are discharged from the diluting device according to the invention directly to the measurement cell of the  
30 analyzer.

In the device according to the invention, the diluting of the slurry sample is carried out so that the sample slurry flow entering the first chamber is conducted onto the inclined surface, which is washed in an essentially same rhythm as the sample cutter takes a sample of the slurry flow to be analyzed.

5 Thus the washing liquid causes the initial dilution of the sample. The slurry sample is further diluted by feeding diluting liquid to the chambers through nozzles connected to liquid conduits. A first nozzle element connected to a liquid conduit, comprising at least one nozzle, feeds diluting liquid to the center part of the first chamber, so that the diluting liquid circulates in essentially every  
10 direction around the liquid conduit. At the same time, the supplied diluting liquid causes agitation in the liquid contained in the chamber, and the delay time of the solids to be analyzed can thus be increased in the chamber, simultaneously diluting the whole sample flow.

15 In order to boost the agitation of the slurry sample to be diluted, diluting liquid is further conducted, through the same liquid conduit, through a second nozzle element comprising at least one nozzle and connected to the liquid conduit in the center part of the second chamber, essentially in all directions with respect to the liquid conduit. In addition, in order to boost agitation, the cross-sectional  
20 area of the flow aperture provided in the top part of the second chamber is made larger than the flow aperture provided in the bottom part of the first chamber.

When using the device according to the invention along with an optical grain  
25 size analyzer, it is important that the sample to be analyzed in the measurement cell of the grain size analyzer, which cell is rectangular in cross-section and is directly connected to the bottom part of the second chamber, is essentially homogeneous on the long side of the measurement cell, but a certain degree of nonhomogeneousness in the sample is allowed on the short  
30 side of the measurement cell, because the measurement is automatically carried out as an average measurement on the side of the short side. Now in the bottom part of the second chamber, where the agitation is good, there are

according to the invention provided essentially high vertical walls that are placed equidistantly with respect to each other, said walls being arranged so that their distance corresponds to the width of the measurement cell on the short sides. On the other hand, the second chamber walls connected to the  
5 long sides of the measurement cell are arranged to be drawn apart, so that the heavy solid particles are allowed to fall on the walls and slide down along the long side of the measurement cell.

The invention is described in more detail below with reference the appended  
10 drawing, where  
figure 1 illustrates a preferred embodiment of the invention, seen from the side,  
figure 2 illustrates an embodiment according to figure 1 in partial cross-section, seen from the direction A-A,  
figure 3 illustrates another preferred embodiment of the invention, seen from  
15 the side and  
figure 4 illustrates an embodiment according to figure 1 in partial cross-section, seen from the direction B-B.

According to figures 1 and 2, the diluting device according to the invention  
20 comprises two chambers, a first chamber, i.e. the top chamber 1 serving as the slurry sample supply chamber, and a second chamber, i.e. the bottom chamber 2 serving as the discharge chamber of the solids contained in the slurry sample, said chambers being mechanically connected on top of each other in an essentially symmetrical manner. The second chamber 2 is further mechanically  
25 connected to a measurement cell 3 of the optical grain size analyzer, said cell being made of glass.

In shape, the top chamber 1 of the device according to the invention is a truncated pyramid and installed so that the bottom of the truncated cone  
30 constitutes the top part 4 of the first chamber. In the embodiment illustrated in the drawings, in the top part 4 of the first chamber there is attached an additional element 19, which as such is not absolutely necessary in the device

according to the invention. The cutting spot of the pyramid of the first chamber 1 forms the bottom part 5 of the top chamber 1, which bottom part is mechanically connected to the second chamber, the bottom chamber 2. The bottom part 5 of the top chamber is by a flange joint 6 connected to the top part 5 7 of the bottom chamber. Because the cross-sectional area of the top part 7 of the bottom chamber is larger than the bottom part 5 of the top chamber, the element of the flange joint 6 that is connected to the bottom chamber 2 is designed so that the heavy particles possibly contained in the sample, which particles have fallen on the walls of the first chamber 1 and roll down along said 10 walls, drop into the second chamber 2 and are remixed in the slurry.

The cross-sectional area of the bottom chamber 2 is reduced, when proceeding towards the discharge aperture of the solids contained in the slurry sample, so that the cross-sectional area of the bottom chamber 2 both in shape and in size 15 corresponds to the rectangular cross-sectional area of the measurement cell 3 of the optical grain size analyzer. The bottom chamber 2 comprises four walls, two opposite walls 9 that approach each other, and two opposite walls 10 that are essentially parallel and thus located equidistantly with respect to each other. On the horizontal level according to the drawings, the opposite parallel 20 walls 10 are shorter than the mutually approaching walls 9, and thus the walls 10 are aligned to match the short walls 21 of the measurement cell 3. Respectively, the walls 9 approaching the discharge aperture for the solids contained in the slurry sample are aligned to match the long walls 22 of the measurement cell 3.

25

In the device according to the invention, in the top part of the top chamber 1, there is installed in an inclined position a sheet 11, and the sample to be analyzed is conducted onto the surface of said sheet through a sample conduit 12 coming from the sample cutter. In addition, through the top part of the top 30 chamber 1, there is installed a liquid conduit 13 inside the device, said liquid conduit extending from the top chamber 1 to the bottom chamber 2. The liquid conduit 13 is installed in the middle part of chambers 1 and 2, so that the liquid

conduit 13 is aligned symmetrically with respect to the walls of both the top chamber 1 and the bottom chamber 2.

Through the liquid conduit 13, liquid is conducted via the nozzles 14 onto the surface of the sheet 11 constituting an inclined surface in order to wash the sheet from time to time, and thus in order to initially dilute the sample. In addition, the liquid conduit is provided with nozzle elements 15 composed of one or several nozzles, through which diluting liquid is conducted to the top chamber 1, and with nozzle elements 16 composed of one or several nozzles, through which diluting liquid is conducted to the bottom chamber 2. The nozzle elements 15 and 16 are composed of several nozzles, in which case the nozzles 15 and 16 direct the diluting liquid essentially in all directions around the liquid conduit 13.

When the device according to the invention is in operation, both the bottom chamber 2 and the top chamber 1 are essentially continuously filled with liquid, and in order to adjust the surface of said liquid, the device comprises surface height adjusting elements 17. By adjusting the operation time of the nozzles 14, the liquid surface 18 is essentially maintained on the level defined by the height adjusting element 17. Advantageously the height of the liquid surface 18 is adjusted on a level where the sheet 11 constituting the inclined surface is located above the liquid surface. In preparation for a possible blocking of the measurement cell 3, the additional element 19 connected to the top chamber 1 is provided with a liquid overflow conduit 20.

25

When the device according to the invention is in operation, the slurry sample obtained from the sample conduit 12 is first conducted onto the surface of the sheet 11 constituting the inclined surface, which surface is then washed by the liquid supplied through the nozzles 14. From the surface of the sheet 11, the slurry flows downwardly to the liquid filling the chambers 1 and 2, where the slurry is diluted and agitated by means of the liquid supplied through the nozzles 15 and 16. On the basis of circulation changes, the solid particles to be

analyzed are obtained in an advantageous position with respect to the measurement cell 3 of the grain size analyzer.

According to figures 3 and 4, the diluting device comprises an downwardly  
5 narrowing chamber 31, with two opposite walls 32 that are parallel with respect to each other and also parallel with the respective walls 35 of the measurement cell 34 of the analyzer that is connected to the chamber 31. The other two opposite walls 37 of the chamber 31 are mutually arranged so that the walls 37 approach each other when proceeding towards the measurement cell 34. The  
10 mutually parallel walls 32 of the chamber 31 are aligned to match the short walls 35 of the measurement cell 34, whereas the mutually approaching walls 37 of the chamber 31 are aligned to match the long walls 38 of the measurement cell 34.

15 The chamber 31 is provided with a liquid conduit 39 in order to conduct the diluting liquid to the chamber 31. Advantageously the liquid conduit 39 is installed in a symmetrical position with respect to the walls 32 and 37 of the chamber 31. Owing to said symmetrical position, the diluting liquid discharged through the nozzle element 40 installed in the liquid conduit 39 and comprising  
20 one or several nozzles is directed in an essentially effective way to the liquid 41 contained throughout the chamber 31 in order to achieve an advantageous agitation. In the top part of the chamber 31, above the liquid surface 42, there is installed an inclined surface 43, to which the slurry sample supplied through the slurry conduit 44 and diluted in the diluting device is conducted. In the vicinity of  
25 said inclined surface 43, there also are installed nozzles 45 and 46 in order to feed washing liquid onto the inclined surface 43 in order to wash the slurry sample and to conduct it into the liquid 41 contained in the chamber. In addition, in the chamber 31 there is installed an adjusting element 48 of the liquid surface height. In case the measurement cell should be blocked, the  
30 chamber is also provided with an overflow conduit 47. Moreover, between the chamber 31 and the measurement cell 34, there are arranged adjusting pieces


49 and 50 in order to advantageously connect the chamber 31 and the measurement cell 34 to each other.

When the embodiment according to figures 3 and 4 is in operation, the slurry  
5 sample that is washed away from the inclined surface 43 is mixed in the liquid  
41 contained in the chamber 31, into which liquid there also is fed diluting liquid  
through the nozzle element 40 connected to the liquid conduit 39 in order to  
maintain an efficient agitation throughout the operation of the diluting device.  
Owing to the efficient agitation, the solid particles to be analyzed are obtained  
10 in an advantageous position with respect to the measurement cell 34 of the  
optical grain size analyzer.

## CLAIMS

1. A device for a continuously operated dilution of a slurry sample, through which device the slurry sample is fed directly into a continuously operated  
5 optical analyzer, such as a grain size analyzer, and which device comprises elements for feeding the slurry sample, elements for feeding diluting liquid and elements for removing solids contained in the slurry, as well as elements for discharging both the liquid contained in the slurry and the liquid used for dilution, **characterized** in that the device comprises at least one downwardly  
10 narrowing chamber (2,31) that is connected to the analyzer measurement cell (3, 34) so that two opposite walls (10, 32) of the chamber (2, 31) are essentially parallel both with respect to each other and with respect to the respective walls (21, 35) of the measurement cell (3, 34).
- 15 2. A device according to claim 1, **characterized** in that in the device, there is installed at least one liquid conduit (13, 39) provided with a nozzle element (16, 40) in order to feed diluting liquid into the chamber (2, 31) and in order to advantageously agitate the liquid contained in the chamber.
- 20 3. A device according to claim 2, **characterized** in that the liquid conduit (13, 39) is installed symmetrically with respect to the walls (10, 32; 9, 37) of the chamber (2, 31).
4. A device according to claim 2, **characterized** in that the liquid conduit (13,  
25 39) is provided with a nozzle element (16, 40).
5. A device according any of the preceding claims, **characterized** in that the device comprises two downwardly narrowing chambers (1, 2) that are in liquid connection with each other and are at least partly filled with liquid.

6. A device according to claim 5, **characterized** in that the first and second chambers (1, 2) of the device are mutually arranged so that the bottom part (5) of the first chamber is connected to the top part (7) of the second chamber.
- 5 7. A device according to claim 5 or 6, **characterized** in that the cross-sectional area of the flow aperture of the top part (7) of the second chamber is larger than the cross-sectional area of the flow aperture of the bottom part (5) of the first chamber.
- 10 8. A device according to any of the claims 5 – 7, **characterized** in that the liquid conduit (13) includes nozzle elements (15, 16) comprising one or several nozzles for feeding diluting liquid into both chambers (1, 2) in order to advantageously agitate the liquid contained in the chambers.






Fig 2




Fig 3




Fig 4

# INTERNATIONAL SEARCH REPORT

1

International application No.

PCT/FI 2004/000055

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G01N 1/38

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6286376 B1 (DAVIDSON, G P ET AL), 11 Sept 2001 (11.09.2001), see whole document. --	1-8
X	DE 4005061 A1 (SALZGITTER INDUSTRIEBAU GMBH), 23 August 1990 (23.08.1990), see whole document. --	1
A	US 4056324 A (GÖHDE, H), 1 November 1977 (01.11.1977), abstract --	1-8
A	US 5311290 A (OLSON, J ET AL), 10 May 1994 (10.05.1994), abstract --	1-8

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

13 May 2004

Date of mailing of the international search report

25 -05- 2004

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Åsa Malm /LR  
Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 2004/000055

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2095827 A (CENTRE SCIENTIFIQUE ET TECHNIQUE DE L'INDUSTRIE TEXTILE BELGE), 29 March 1982 (29.03.1982), abstract --	1-8
A	FI 57662 B (BOLIDEN AB), 28 June 1976 (28.06.1976), abstract --	1-8
A	EP 0604307 A1 (LYONNAISE DES EAUX-DUMEZ), 29 June 1994 (29.06.1994), abstract --	1-8
A	WO 03046518 A1 (HOLMEN AB), 5 June 2003 (05.06.2003), abstract --	1-8
A	US 4684251 A (BROUWER, G ET AL), 4 August 1987 (04.08.1987), abstract --	1-8
A	FI 110033 B (OUTOKUMPU OYJ), 10 January 2000 (10.01.2000), abstract -- -----	1-8

## INTERNATIONAL SEARCH REPORT

Information on patent family members

31/03/2004

International application No.

PCT/FI 2004/000055

US	6286376	B1	11/09/2001	AT	226770	T	15/11/2002
				AU	7782898	A	30/12/1998
				DE	29802975	U	30/04/1998
				DE	69808958	D,T	27/02/2003
				EP	1021866	A,B	26/07/2000
				GB	2333836	A	04/08/1999
				GB	9801667	D	00/00/0000
				ZA	9900632	A	17/02/2000
DE	4005061	A1	23/08/1990	DE	59008504	D	00/00/0000
				EP	0382882	A	22/08/1990
				EP	0403034	A,B	19/12/1990
				SE	0403034	T3	
				ES	2070271	T	01/06/1995
US	4056324	A	01/11/1977	CH	594244	A	30/12/1977
				DE	2521236	A,B,C	18/11/1976
				GB	1507285	A	12/04/1978
US	5311290	A	10/05/1994	AU	5104793	A	26/04/1994
				CA	2145275	A,C	14/04/1994
				WO	9408223	A	14/04/1994
GB	2095827	A	29/03/1982	AU	559124	B	26/02/1987
				AU	8222982	A	07/10/1982
				BE	892719	A	30/09/1982
				CH	665480	A	13/05/1988
FI	57662	B	28/06/1976	AU	8767375	A	23/06/1977
				CA	1038197	A	12/09/1978
				DE	2558377	A,C	08/07/1976
				FI	753642	A	28/06/1976
				GB	1496614	A	30/12/1977
				SE	379424	B,C	06/10/1975
				US	3999438	A	28/12/1976
EP	0604307	A1	29/06/1994	FR	2699682	A,B	24/06/1994
WO	03046518	A1	05/06/2003	SE	520297	C	24/06/2003
				SE	0103969	A	29/05/2003
US	4684251	A	04/08/1987	AU	579230	B	17/11/1988
				AU	5499486	A	25/09/1986
				EP	0195488	A	24/09/1986
				GB	2172713	A,B	24/09/1986
				GB	8507521	D	00/00/0000
				JP	61223634	A	04/10/1986
FI	110033	B	10/01/2000	AU	758411	B	20/03/2003
				AU	3796599	A	03/02/2000
				CA	2277015	A	09/01/2000
				FI	981581	A	10/01/2000
				US	6148679	A	21/11/2000
				ZA	9904365	A	11/01/2000